

Rack Mount Media Converter

Rack mount Media Converter is a 2U rack mount media converter combine for the equipments centralized management in the central office. It provides 16 slots to load various type of media transceivers. It is supporting to hot plugable and friendly user management.

Features

- 19" 2U rack panel
- 14 or 16 slots for media converter module
- 10M, 100M, 1000M media converter optional
- Independent controlling for each plug card
- Supporting to hot plug operation
- Centralized power supply
- SFP DMI function activate
- 850nm, 1310nm, 1550nm and DWDM/ CWDM wavelength ruled by ITUT
- Remote power off alarming
- Economical management function with
- Web management activate



Specification

Parameter	14-Slot	16-Slot
Access Method	1X10/100/1000M RJ45 1X1000Base-FX	
Color	Black or Silvery	
Standard	IEEE802.3, IEEE802.3u, IEEE802.3Z, IEEE802.3x	
Wavelength	850nm/1310nm/1550nm	
Connector	SC,FC,ST,LC	
Power Dissipation	<3W	
Power input	AC 100 ~ 260V, 50~60Hz; or DC48V	
Power output	DC +5V 12A(single power) or 24A(dual power)	
Power Protection	Circuit- breaker when over voltage, over current ,over flow and short circuit	
Operating Temperature	0 ~ 50°C	
Humidity	5%~90%	
Storage Temperature	-40~ 70°C	
Dimensions	485mm x 245mm x 90mm (Standard 19-Inch, 2U height)	156mm (W)×128mm(D)×32 mm(H) (standalone) 112.8mm (W)×77.2mm(D)×23 mm(H) (Card)

