



## Specification

# SC Adapter With Internal Shutter

### Description

Fiber optic adapter is to achieve the same or different optical fiber connectors docking in optical links, make the light path connected under the small loss. It is to put the fiber of two surface precision docking, so that the optical output of light energy to the maximum coupling in the receiving optical fiber, and since it entered the optical link to minimize the effects on the system. Widely used in optical fiber distribution frame (ODF), fiber optic communications equipment, instruments, etc., superior performance, stable and reliable.

### Application

- CATV
- Telecommunication networks
- Local Area Networks (LANs)
- Data processing networks
- Test equipment
- Premise installations
- Gigabit Ethernet
- Metro

### Features

- Low insertion loss and back reflection loss
- High precision alignment
- Compact design
- With/Without flange
- Choice of housing material and sleeve material
- Telcordia, ANSI, TIA/EIA, NTT and JIS compliance

### Specification

Item	Specification
Insertion Loss	<0.20dB
Durability	<0.20dB typical change, 1000 matings
Operating Temperature	-40 ~ 85°C(PBT) / -25 ~ 70°C(ABS)

### Availability

Flange Type	Structure Type	Housing Color
Flange	Simplex	SM/PC - Blue
No Flange	Duplex	SM/APC - Green
		MM/PC - Beige/Aqua/Magenta/Black



Internal Shutter

